MATERIAL SAFETY DATA SHEET For Coatings, Resins and Related Materials

Manufacturer: Crawford Laboratories, Inc.	Emergency Phone: 800-424-9300
Chicago IL 60609 Product Class: ACTIVATOR Trade Name : SATIN FLOROPOXY Product Code : U0-173 C.A.S. Number: SEE BELOW	! Hazard Ratings: Health - 3 ! none -> extreme Fire - 1 ! 0> 4 Reactivity - 0 !
SECTION II - HAZARDOUS INGREDIENTS	
Wei	ght Exposure Limits VP * ACGIH/TLV OSHA/PEL mm HG 0-75 Undetermined 1. use severe .ndness and
NONYLPHENOL 84852-15-3 5 PHENYL CARBINOL 100-51-6 5 May contain as impurities the following benzaldehyde (CAS# 100-52-7) dibenzyl ether (CAS# 103-50-4) hydroquinone monomethyl ether (CAS#	5-20 Undetermined 0.1 g items:
* SECTION 313 SUPPLIER NOTIFICATION Ingredients with * above are subject to reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 of 40 CFR 372.	
SECTION III - PHYSICAL DATA	
Evap. Rate: n-Butyl Acetate Li	apor Density: Heavier than Air. Equid Density: Lighter than Water. gt per gallon: 8.0 Pounds.
SECTION IV - FIRE AND EXPLOSION HAZARD DATA	
Flammability Class: Flash Point: 194 F tcc LEL: -EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL -SPECIAL FIREFIGHTING PROCEDURES: AS IN ANY FIRE, PREVENT HUMAN EXPOSURE TO FIRE, SMOKE, FUMES OR PRODUCTS OF COMBUSTION. EVACUATE NON-ESSENTIAL PERSONNEL FROM THE FIRE AREA. FIRE FIGHTERS SHOULD WEAR FULL-FACE, SELF- CONTAINED BREATHING APPARATUS AND IMPERVIOUS PROTECTINVE CLOTHING. WATER MAY BE USED TO KEEP FLAMMABLE STRUCTURES WET.	

Crawford Laboratories, Inc.

Material Safety Data Sheet for: U0-173 _______ SECTION IV - FIRE AND EXPLOSION HAZARD DATA (cont.) -UNUSUAL FIRE & EXPLOSION HAZARDS: SEALED CONTAINERS MAY EXPLODE IF OVERHEATED. SECTION V - HEALTH HAZARD DATA ______ -PERMISSIBLE EXPOSURE LEVEL: CARE SHOULD BE TAKEN TO ASSURE THAT THE EXPOSURE LIMITS SHOWN IN SECTION II ARE NOT EXCEEDED. WHEN IN DOUBT - WEAR AN APPROVED RESPIRATOR AND ORDER AIR SAMPLING TESTS. (SEE SECTION VIII). -EFFECTS OF OVEREXPOSURE: GENERAL EFFECTS FOR THIS TYPE OF PRODUCT: MAY CAUSE INJURY TO SKIN FOLLOWING REPEATED OR PROLONGED CONTACT AND MAY CAUSE SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES. EYE CONTACT MAY CAUSE SEVERE IRRITATION INHALATION MAY CAUSE IRRITATION TO NOSE, THROAT OR LUNGS INGESTION MAY BE HARMFUL IF SWALLOWED -FIRST AID: --EYE CONTACT-FLUSH WITH PLENTY OF FRESH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. --INHALATION-REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION. KEEP VICTIM WARM AND COMFORTABLE. NEVER GIVE AN UNCONSCIOUS PERSON LIQUIDS. --INGESTION-IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. ONLY INDUCE VOMITING ON INSTRUCTIONS OF PHYSICIAN. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. --SKIN CONTACT- FLUSH WITH WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. FOLLOW BY WASHING WITH SOAP AND WATER. DO NOT REUSE CONTAMINATED CLOTHING OR SHOES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IF STICKY, USE WATERLESS CLEANER FIRST. ------SECTION VI - REACTIVITY DATA STABLITY: [] Unstable [x] Stable HAZARDOUS POLYMERIZATION: [] May occur [x] Will not occur -INCOMPATABILITY:

STRONG ACIDS, OXIDIZERS

STRONG ACIDS, OXIDIZERS -HAZARDOUS DECOMPOSITION PRODUCTS:

TOXIC FUMES AT DECOMPOSITION TEMPERATURES.

SUCH AS CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN,

-CONDITIONS TO AVOID:

HF.

Crawford Laboratories, Inc. Material Safety Data Sheet for: U0-173

SECTION VII - SPILL OR LEAK PROCEDURES

-STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED COMPLETELY ABSORB WITH INERT MATERIAL (VERMICULITE), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA WITH WATER BUT PREVENT WASHINGS FROM ENTERING SEWERS AND WATERWAYS.

-WASTE DISPOSAL METHOD:

PLACE IN CLOSED CONTAINERS. DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATIONS. CONTACT AN APPROVED DISPOSAL FACILITY.

SECTION VIII - SPECIAL PROTECTION INFORMATION:

-RESPIRATORY PROTECTION:

PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATORS SHALL BE USED DURING APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS.

-VENTILATION:

EFFECTIVE ENGINEERING CONTROLS SHOULD BE USED WHEREVER POSSIBLE. SOLVENT FREE COATINGS MAY PRODUCE VAPORS.

-PROTECTIVE GLOVES:

NEOPRENE RUBBER GLOVES.

-EYE PROTECTION:

WEAR APPROVED SAFETY GOGGLES AND/OR FACE SHIELD.

-OTHER PROTECTIVE EQUIPMENT:

HAVE EYE BATH AVAILABLE AND SAFETY SHOWER AVAILABLE.

SECTION IX - SPECIAL PRECAUTIONS

-PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

STORE AWAY FROM FLAMES AND HIGH TEMPERATURES. AVOID PROLONGED SKIN CONTACT. AVOID BREATHING VAPORS.

-OTHER PRECAUTIONS:

NOTE:

All information and opinions in this report are based on experience and computer programming which we believe to be reliable. We believe that the information contained herein is current as of the date of this report. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of Crawford Laboratories, Inc, it is the user's obligation to determine the conditions of safe use of this product.

Crawford Laboratories, Inc. makes no warranty, expressed or implied, as to the accuracy of the information and opinions, and assumes no responsibility for any damage to person, property or business arising from such use.

text04