

Material Safety Data Sheet
Crawford Laboratories, Inc.

Section 1-Product and Company Identification

Product Name: Florocrete Part C
Chemical Name: Aggregate Blend
Recommended Use: Use with Florocrete SL, RT, HD, SLX and TL
Company Identification: Crawford Laboratories, Inc.
4165 S. Emerald Ave.
Chicago, Illinois 60609

Emergency Contact: Chemtrec
Phone: 800-424-9300

Preparer: DS
Product Support: 773 376-7132
Date Issued: 08-26-2011
Number of pages: 4

Section 2 - Composition / Information on Ingredients

Crystalline Silica (Quartz) CAS 14808-60-7	10 mg/m ³ / %SiO ₂ +2	OSHA PEL	Respirable Dust
	30 mg/m ³ / %SiO ₂ +2	OSHA PEL	Total Dust
	.05 mg/m ³	NIOSH REL	
	.025 mg/m ³	ACGIH TLV	
Portland Cement CAS 65997-15-1	5 mg/m ³	OSHA PEL	Respirable Dust
	15 mg/m ³	OSHA PEL	Total Dust
	5 mg/m ³	NIOSH REL	Respirable Dust
	10 mg/m ³	NIOSH REL	Total Dust
	10 mg/m ³	ACGIH TLV	
Calcium Hydroxide CAS 1305-62-0	5 mg/m ³	OSHA PEL	Respirable Dust
	15 mg/m ³	OSHA PEL	Total Dust
	5 mg/m ³	NIOSH REL	
Glass Oxide CAS 65997-15-3	5 mg/m ³	OSHA PEL	Respirable Dust
	15 mg/m ³	OSHA PEL	Total Dust

OSHA Permissible Exposure Limits (PEL) and ACGIH Threshold Limit Values (TLV) are an 8-hour time-weighted average (TWA) concentration during a 40-hour workweek; NIOSH Recommended Exposure Limits (REL) is for up to a 10-hour workday during a 40-hour workweek.

Section 3 – Hazards Identification

Emergency Overview: Lung injury and cancer hazard. Material when wet or when dry material is exposed to moist areas of the body can cause tissue destruction (skin, eyes) in the form of chemical (caustic) burns. Do not breathe dust. Avoid contact with material.

Potential Health Effects:

Acute: The material irritates the respiratory tract and is corrosive to the eyes and the skin.

Chronic: The material may have effects on the lungs, resulting in fibrosis (silicosis). The material is carcinogenic to humans. Repeated or prolonged contact with skin may cause dermatitis, or skin sensitization.

Routes of Exposure - Overexposure or Hazard Symptoms:

Inhalation: Coughing, Sore throat. Burning sensation.

Eye Contact: Redness. Pain. Severe chemical burns.

Skin Contact: Redness. Pain. Skin burns. Blisters.

Ingestion: Burning sensation. Abdominal pain and cramps. Vomiting.

See Section 11 - Toxicological Information

Section 4 - First Aid Measures

Inhalation: Seek fresh air. If irritation persists, seek medical attention.

Eye Contact: Flush eyes immediately and thoroughly with water. Seek medical attention.

Skin Contact: Wash exposed skin with soap and water. If irritation persists, seek medical attention.

Ingestion: Rinse mouth. Dilute by drinking large quantities of water. Do not induce vomiting. Seek Medical attention.

Section 5 - Fire Fighting Measures

Extinguishing Media: Material is not flammable, non-combustible and non-explosive. Use media appropriate for surrounding fire. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Seek medical attention.

Special Fire Fighting Procedures: Full protective equipment including self-contained breathing apparatus should be used.

Section 6 - Accidental Release Measures

Accidental Release: Use personal protective equipment recommended in Section 8. Clean up using dustless methods to minimize generation and distribution of respirable silica/cement particles. Sweep material into container and move to a safe place. Avoid contact with wet product. Avoid using compressed air and material entering sewers, drains or surface waters.

Section 7 - Handling and Storage

Handling: Use adequate ventilation and/or dust collection to keep dust below exposure limits as outlined in Section 2. Handle the product in accordance with strict hygiene and safety practices. Do not breathe dust and prevent dispersion of dust. Avoid contact with eyes and skin. Wear appropriate PPE as outlined in Section 8 when handling product.

Storage: Store in a dry, well-ventilated area out of direct sunlight. Keep containers closed. Protect from damage. Keep separated from strong acids.

Section 8 - Exposure Controls/Personal Protection

Local Exhaust: Use sufficient local exhaust to reduce the level of respirable dusts to below the PEL.

Respiratory Protection: Use NIOSH-approved air purifying or supplied-air respirator where airborne concentrations are expected to exceed exposure limits

Eye Protection: Use safety glasses, goggles, or face shield. Contact lenses should not be worn when working with this product.

Skin Protection: Use impervious gloves and clothing. Wash exposed skin with soap and water, and launder soiled work clothing. Avoid contact with wet material.

Use good personal hygiene. Do not eat, drink, or smoke when handling this product.

See Section 2 - Composition / Information on Ingredients for information on exposure limits.

Section 9 - Physical and Chemical Properties

Physical State: Solid

Specific Gravity (Water = 1): NE

Solubility in Water: Slightly

Vapor Pressure: NE

Melting Point: NE

Boiling Point: NE

Evaporation Rate (Butyl Acetate = 1): NE

Vapor Density: NE

Section 10- Stability and Reactivity

Stability: Stable

Conditions to avoid: Unintentional contact with water.

Hazardous Polymerization: Cannot occur.

Chemical Incompatibility (Materials to Avoid): The material may react with strong oxidants, acids and aluminum metals. The material may react with water forming hardened hydrated compounds, releasing heat and producing an alkaline solution.

Hazardous Decomposition Products: Adding water to Portland produces (caustic) calcium hydroxide.

Section 11 - Toxicological Information

Product based information: There are limited toxicological data available for this product. Exposure can occur with the dry product or to dusts when hardened mortar is ground, cut, drilled, sanded or otherwise disturbed. Inhalation of the dusts can cause respiratory tract irritation with coughing and nasal discharge. Shortness of breath and reduced pulmonary function may also result from inhalation. Alveolar damage and pulmonary edema resulted in animal studies from exposure to the dry product.

Prolonged overexposure to the respirable dust can cause pneumoconiosis, silicosis (a permanent fibrotic lung disease) and potentially lung cancer. The dust from the material can cause inflammation of the lining tissue in the nose and inflammation of the cornea. Contact with the eyes may cause burns and permanent damage to the eyes. Skin contact with the wet product can cause burns (corrosive). Repeated or prolonged skin contact with the wet product can cause drying of the skin, dermatitis and possibly allergic skin reactions.

Carcinogen:

IARC-Yes

NTP-Yes

OSHA-No

See also Section 3 – Hazards Identification

Section 12 – Ecological Information

Ecotoxicity: No data available

Section 13 - Disposal Considerations

General: Disposal of the Material should be in accordance with the applicable federal, state and local laws and regulations.

Section 14 Transport Information

General Transport Statement: This product does not require classification by DOT.

Section 15 – Regulatory Information

SARA Title III (Superfund Amendments and Reauthorization Act)
Section 302 Extremely Hazardous Materials: None

Section 304 Notification of Accidental Release: None

Sections 311/312 Hazard Categories:

Immediate (Acute) Health Effects: Yes

Delayed (Chronic) Health Effects: Yes

Section 313 Toxic Chemical Release Reporting: None

DHS (Department of Homeland Security) Appendix A: None

Section 16- Other Information

User's Responsibility: The OSHA Hazard Communication Standard 29 CFR 1910.1200 require that this material Safety Data Sheet be made available to your employees who handle or may be exposed to this product. Educate and train your employees regarding applicable precautions. Instruct your employees to handle this product properly.

Disclaimer: All information and opinions in this report are based on experience and computer programming which we believe to be reliable. We believe that the information contained herein is current as of the date of this report. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of Crawford Laboratories, Inc, it's the user's obligation to determine the conditions of safe use of this product.

Crawford Laboratories, Inc. makes no warranty, expressed or implied, as to the accuracy of the information and opinions, and assumes no responsibility for any damage to person, property or business arising from such use.

End of Material Safety Data Sheet