

Florock Care and Maintenance

Florock Seamless Flooring Systems provide durable floors that are not only decorative, but also very easy to maintain. A daily program of routine sweeping and occasional light scrubbing will help your Florock floor retain its attractive appearance and superior performance for years to come.

SWEEPING

Sweep floors daily with a broom or soft-bristled mechanized sweeper. This will extend the life of the finish and will result in longer periods between recoats.

SCRUBBING

Once-weekly scrubbing is generally sufficient to keep your Florock floor looking great. High traffic areas may require more frequent cleaning. Use a mop and bucket or soft-bristled mechanized scrubber as needed.

SPILLS

Any liquid spill can pose a slip hazard and should be attended to immediately. Harsh materials, such as caustics, acids, and solvents can cause damage to your floor coating. Spills of this kind should be cleaned immediately. Consult your Florock Representative regarding the chemical resistant requirements of your specific floor.

To clean grease, chemical or oil spills:

1. Use circular motion to wipe up spill. Try to avoid spreading.
2. Scrub the area with Mild Detergent Cleaner.
3. Dispose of chemical waste in accordance with governing regulations.

SCRATCHES AND GOUGES

Heavy machinery, pallets or sharp objects should not be slid or scraped along the floor. This can result in cuts or gouges.

STAINS

Should staining occur, attempt removal first with a mild solution, progressing to stronger cleaners until stain disappears. It is always a good to wear hand and eye

protection when working with chemicals. Residue from a spill that has dried can be removed with a plastic tool (take care not to scratch the surface). Then use a mild Detergent cleaner to remove the stain. If the stain persists, contact you Florock Representative for assistance.

PLASTICIZER MARKS

Plasticizer marks, which are sometimes referred to as shadows, are permanent marks left in floor coatings. These marks are caused by chemicals called plasticizers that are used in the manufacturing of rubber wheels. After the wheels are in contact with the floor for a period of time, the plasticizers seep into the floor coating, leaving dark spots on the floor.

While these marks cannot be removed, they can be hidden by sanding and recoating the floor using a Florock colored flooring system. However, the best way to approach the problem of plasticizer marks is to prevent them from appearing in the first place. This can be done by placing a barrier between the tires and the floor.

RECOAT

Periodic application of the topcoat will ensure a tight seal on your floor surface, preventing soil and moisture damage. With proper maintenance, your Florock System floor will provide many years of service.

Disclaimer:

All statements and recommendations are based on experience we believe to be reliable. The use or the application of these products being beyond the control of the Seller or Manufacturer, neither Seller nor Manufacturer make any warranty, expressed or implied, as to results or hazard from its use. The suitability, risk and liability whatsoever of a product for an intended use shall be solely up to the User.